

Standard **T&B Catalog Number:**

UPC Number: Status: **Description:**

TY24MX 78621082644 Active

Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to 85 Degrees Celsius (185 F) for Indoor Applications, UL/EN/CSA62275 Type 2/21 Rated for AH-2 Plenum, Length of 139.7mm (5.5 Inches), Width of 3.56mm (0.14 Inches), Thickness of 1.31mm (0.052 Inches), Tensile Strength Rating of 135 Newtons (30 Pounds), Military Specified (MIL-SPEC MS3367-5-0), Bulk Pack

> Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device

Features	

	insures both maximum strength and the right tight- ness every time.
	Because there are no notches, Ty-Rap ties provide
	an infinite number of locking positions while fasten-
	ing the tie at the precise bundle diameter needed.
	The No-Slip Tail provides easy grip during tension-
	ing. Ty-Rap ties feature a unique friction surface de-
	signed to reduce slippage during installation.
	Smooth, notchless body reduces stress concentra-
	tion points under tension, making the tie stronger and lower profile than notched body ties. Ribbed and Stippled body grips the bundle and prevents
	slippage. Rounded edges protect insulation, pre- venting sharp edges from damaging cables.
General	terning only ougos norr damaging cables.
Material	Nylon 6.6 Weather Resistant
Color	Black
Dimension Information	
Nominal Length (inches)	6
Length (inches)	5.5
Width (inches)	.140
Max. Wire Bundle Diameter (inches)	1.125
Specifications	
Military Standard Part No.	MS3367-5
Temperature Rating	-40°F to 185°F
Flammability Rating	UL 94 V-2
Tooling	
Application Tools	ERG50, WT1-TB
Packaging	
T&B Order Multiple	1000
T&B Inner Pack	1000
Package in Units	10000
Package Type	Bulk
T&B Sold in UOM	Each
T&B Weight Per UOM	1 lbs. per 100



Application Support

Material Selection Guide Available Colors Available on Website Available on Website

Certifications

RoHS Compliance

Yes

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@thb.com

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com